

WATER BLASTING HOSE



An-Flex WB 750 Series (10,000 PSI)

HOSE SIZE	I.D.		O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	INCH	MM	INCH	MM	BAR	PSI	BAR	PSI	INCH	MM	LBS/FT
6	1/4	6.4	0.70	17.8	750	10875	1875	27100	5.10	130	0.412	0.614
10	3/8	9.5	0.84	21.4	750	10875	1875	27100	7.09	180	0.511	0.760
12	1/2	12.7	0.96	24.6	750	10875	1875	27100	9.06	230	0.645	0.960
19	3/4	19	1.26	32.2	750	10875	1875	27100	11.81	300	1.677	2.500

An-Flex WB 850 Series (12,000 PSI)

HOSE SIZE	I.D.		O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	INCH	MM	INCH	MM	BAR	PSI	BAR	PSI	INCH	MM	LBS/FT
6	1/4	6.4	0.70	17.8	850	12330	2200	31880	5.10	130	0.412	0.614
10	3/8	9.5	0.84	21.4	850	12330	2200	31880	6.10	155	0.526	0.784
12	1/2	12.7	0.96	24.6	850	12330	2200	31880	7.90	200	0.684	1.020
19	3/4	19	1.29	32.5	850	12330	2200	31880	9.80	250	1.295	1.930
25	1	25	1.76	44.6	850	12330	2200	31880	11.80	300	2.247	3.350

An-Flex WB Waterblasting Hose

- TUBE : oil resistant synthetic rubber
- REINFORCEMENT : 4 - 6 spirals of very high tensile steel wire
- COVER : oil, weather and abrasion resistant rubber cover
- TEMPERATURE RANGE : -40 °C to +100 °C
(-40 °F to +212 °F)
- COMPLIANCE : complies to International standard specification AS/NZ 4233.2
prEN 1829-2 & DIN 20023T1

WATER BLASTING HOSE



An-Flex WB 1000 Series (15,000 PSI)

HOSE SIZE	I.D.		O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	INCH	MM	INCH	MM	BAR	PSI	BAR	PSI	INCH	MM	LBS/FT
10	3/8	9.5	0.85	21.4	1000	14500	2500	36250	7.09	180	0.511	0.760
12	1/2	12.7	0.96	24.5	1100	16000	2758	40000	7.37	200	0.912	1.360
19	3/4	19.0	1.26	32.0	1000	14500	2500	36250	12.2	310	1.677	2.500

An-Flex WB 1400 Series (20,000 PSI)

HOSE SIZE	I.D.		O.D.		WORKING PRESSURE		BURST PRESSURE		MINIMUM BEND RADIUS		WEIGHT	
	DN	INCH	MM	INCH	MM	BAR	PSI	BAR	PSI	INCH	MM	LBS/FT
6	1/4	6.4	0.811	20.6	1400	20290	3550	51450	5.90	150	0.617	0.920
10	3/8	9.5	0.944	24.0	1400	20290	3550	51540	7.08	180	0.92	1.370
12	1/2	12.7	1.14	29.0	1400	20290	3650	52900	9.05	230	1.275	1.900

An-Flex WB Waterblasting Hose

- TUBE : oil resistant synthetic rubber
- REINFORCEMENT : 4 - 6 spirals of very high tensile steel wire
- COVER : oil, weather and abrasion resistant rubber cover
- TEMPERATURE RANGE : -40 °C to +100 °C
(-40 °F to +212 °F)
- COMPLIANCE : complies to International standard specification AS/NZ 4233.2
prEN 1829-2 & DIN 20023T1